

TERMINAL REQUIREMENTS:

- TWIC
- DRIVER MUST HAVE **GATE CODE** FOR ALL MISSIONS
- SAFETY VEST MUST BE WORN
- FRONT LICENSE PLATE MUST BE UNOBSTRUCTED (NO COVERS, SHIELDS, ETC.)
- CELLULAR PHONES AND OTHER ELECTRONIC DEVICES CANNOT BE USED WHILE TRAVELING

1. Present your TWIC to security guard at entrance gate and then drive thru the AGS Inbound Portals. (Terminal Speed Limit is **25 mph**, AGS Portal Speed Limit is **7 mph**.)
2. Proceed to the Inbound Inspection canopy. Lift card reader cover and place CDL or TWIC on scanner (**CDL/TWIC must be removed from case or protective covering before placed on scanner**.) Once completed, follow instructions displayed on the Kiosk's screen. Use keypad located on Kiosk to enter information.








3. You will be issued a "**Routing Slip**" that explains what you are to do for your mission.

Receive Loaded Container		Apr 29, 1999
Job Number	ORION Number	Tractor
0809	976730	3150
Shipping Line (5555)		
BEST SHIPPING LINE		
Trucking Company (BT)		
BEST TRUCKING CO.		
Seal	Seal (add)	
009223		
DRY 40'66"		
FMCU 201358	→	DE020
CHAZ 304930	→	EK017
EXIT		

Section: D
Row: E
Slot: 020

Section: E
Row: K
Slot: 017A

ICON MEANINGS

	Direction of Movement
 PF020	Container Stack with Location
 CD036	Wheeled Row with Location
 MOSK 41028	Bare Chassis
 MOLU216438	Married Container & Chassis
	Leave Terminal After Gate Out
	Follow Given Instructions

4. After collecting "**Routing Slip**," place TWIC on security scanner to raise barrier arm and exit inbound lane.
5. After completing all tasks on the "**Routing Slip**," drive through the Outbound Portal and proceed to the outbound lane Kiosk.

Communication from Container Handler

- 1 horn beep – pull forward
- 2 horn beeps – back up
- 1 horn beep while moving – Stop

6. Follow the instructions on the Kiosk's screen. Use keypad to enter required information.
7. Remove the printed Carrier Interchange from the Kiosk. Place TWIC on security scanner to raise barrier arm and exit outbound lane.
8. Proceed through RPM.
9. Present your Carrier Interchange to Guard Gate.

Solutions Center Contact Information

Voice: (843) 579-4433

Fax: (843) 628-2444

Email: solutionscenter@scspa.com